

CLOPAY COMMERCIAL – MODEL 3730

**energy series** with intellicore®



Model 3730, 12'2" x 14' doors, shown with 24" x 12" Lites

CONSTRUCTION	EFFICIENCY	WARRANTY
<b>3"</b> THICKNESS	<b>22.2</b> R-VALUE	<b>10YR</b> LIMITED CONSTRUCTION



## POLYURETHANE INSULATED STEEL DOORS WITH MINOR RIBS

Clopay Model 3730 is for commercial and industrial facilities where ease of maintenance, versatility, durability and high R-value considerations are all important.

- **Intellicore®** insulation provides the highest energy efficiency, while remaining environmentally friendly.
- **Steel-Sandwich Construction** enhances durability and strength.
- **3-Stage Paint Process** delivers a maintenance-free finish.
- **Thermal Break** enhances insulating properties for extreme energy efficiency.
- **Optional Accessories** add functionality while complementing the building.



Panels are pre-painted inside and out to inhibit rust. Hot-dipped, galvanized steel is painted with primer and given a tough oven-baked polyester top coat to provide the most rust-resistant steel door available. Ten-year warranty against rust-through.


[clopaycommercial.com](http://clopaycommercial.com)

## PANEL DESIGN



Minor Ribbed

## COLOR OPTIONS



Standard White



Chocolate

Due to the printing process, colors may vary.

## CUSTOM PAINT OPTION



Color Blast™ offers more than 1,500 Sherwin-Williams® color options to complement your building design. Clopay's durable factory finish has been thoroughly tested and is backed by a five-year warranty.

Due to solar reflective formulation to meet greater than a 38 LRV some colors may not be available.

## FEATURES

### STANDARD HARDWARE

18 gauge single-end stiles; 16 gauge double-end stiles

PVC vinyl astragal with aluminum retainer

Commercial 10-ball steel rollers (nylon tires available)

Steel step plate and lift handle

Heavy-duty galvanized end stiles

Inside slide lock for increased security

19 gauge steel hinge support plates

2" (50.8 mm) or 3" (76.2 mm) track

10,000 cycle springs

Galvanized aircraft cable with minimum 7:1 safety factor

Variety of track configurations to meet building specifications

### MATERIALS AND CONSTRUCTION

Panel Thickness 3" (76.2 mm)

Insulation CFC and HCFC-free Intellicore® polyurethane

R-value 22.2\*

Thermal Break Continuous foam

Exterior Steel 27 gauge (.016" min.) (.41 mm)

Interior Steel 28 gauge (.015" min.) (.38 mm)

Exterior Surface Stucco embossed, minor ribbed

Max Width 30'2" (9.2 m)

Max Height 24' (7.3 m)

Exterior Colors Standard White and Chocolate. Also available in Color Blast™

Interior Color Standard White

Limited Warranties 10-Year delamination  
10-Year rust-through  
1-Year material and workmanship

\*Calculated door section R-value is in accordance with DASMA TDS-163.

For special sizes, applications and options, consult Commercial Information Assistance (CIA) at 1-800-526-4301.



For more information on these and other Clopay products, call 1-800-526-4301 or visit [clopaycommercial.com](http://clopaycommercial.com)



©2015 Clopay Building Products Company, Inc., a Griffon company.

## ADDITIONAL OPTIONS

### WINDOW OPTIONS



24" x 8"



24" x 12"

Available with nominal insulated triple pane DSB glass.

### HEAVY-DUTY HARDWARE (where not standard)



Double-end hinge



3" Track



Outside keyed lock

### HIGH CYCLE SPRINGS



25,000, 50,000 or 100,000 cycle springs available.

### EXHAUST PORT



Can be cut into any type of sectional door. Available in select sizes.



WINDCODE® doors are available in many sizes and pressure ratings.



Upgrade your standard door with industrial-grade components.

### DISTRIBUTED BY:

